WILKERSON FRL'S B18 COMPACT FILTER/REGULATOR



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 06:57 PM

SKU
: 26061

BRAND
: DIXON VALVE

MODEL
: B18-04AGMB

Applications:
Over-under units are space savers and provide for installation in tight areas.
One common inlet/outlet for both filter and regulator saves on piping costs.

Use:
To increase regulated pressure, pull adjusting knob and turn clockwise. To reduce pressure, turn knob counter clockwise. To lock knob, push down.
Two 1/4" gauge ports located on the front and rear faces of the body. These ports may be used as additional regulated ports or for pressure gauges. Plug unused port(s).

Features:
10-250 PSIG adjusting range for metal bowl with sight glass
5 micron element
1.72 oz. bowl
Self-relieving standard
Spring-loaded diaphragm
Metal bowl supplied with GC240 gauge

Safety notes:
FRL\'s are designed for air service only, unless otherwise indicated.
SCFM ratings at 100 PSIG inlet pressure
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Description	Automatic Drain, Metal Bowl with Sight Glass
Factory Part Number	B18-04AGMB
Flow	121 SCFM
Mandatory Pkg/Box Qty	1
Maximum Operating Pressure	250 PSIG (17.2 Bar)
Port	1/2"
Temperature Range	32°F to 150°F (0°C to 65.5°C)
Weight Lb	1.9300

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us