WILKERSON FRL'S B28 STANDARD FILTER/REGULATOR



* Referential image
** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 11/23/2026 08:36 PM

SKU
: 26072

BRAND
: DIXON VALVE

MODEL
: B28-06AG

Applications:
Over-under units are space savers and provide for installation in tight areas.
One common inlet/outlet for both filter and regulator saves on piping costs.

Use:
To increase regulated pressure, pull adjusting knob and turn clockwise. To reduce pressure, turn knob counter clockwise. To lock knob, push down.

Features:
5-125 PSIG adjusting range for transparent bowl with guard
5 micron element
2.87 oz. bowl
Self-relieving standard
Spring-loaded diaphragm
Two 1/4" gauge ports located on the front and rear faces of the body. These ports may be used as additional regulated ports or for pressure gauges. Plug unused port(s).
Transparent bowl supplied with GC230 gauge

Safety notes:
FRL\'s are designed for air service only, unless otherwise indicated.
SCFM ratings at 100 PSIG inlet pressure
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Description	Automatic Drain, Transparent Bowl and Guard
Factory Part Number	B28-06AG
Flow	235 SCFM
Mandatory Pkg/Box Qty	1
Maximum Operating Pressure	150 PSIG (10.3 Bar)
Port	3/4"
Temperature Range	32°F to 125°F (0°C to 52°C)
Weight Lb	2.2800

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us