AIR BLOW CHECK VALVE QUICK-CONNECT PLUG



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 08:53 PM

SKU
: 8118

BRAND
: DIXON VALVE

MODEL
: B45AB-R200

Applications:
The air blow check valve is designed to pressurize lines with air to clean out product or cleaning solutions. It is fail-safe because the simple air-to-open, spring-to-close mechanism prevents backflow. Can be used with a check valve.

Specifications:
3A authorized 58-00

Construction:
EPDM stem seat and gasket

Note:
Filter disc (optional) must be used when installed for Accepted Practice 3A 604-05, Supplying Air under Pressure in Contact with Milk, Milk products and Product Contact.

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	B45AB-R200
Material	316L Stainless Steel
Maximum Operating Pressure	145 PSI
Maximum Temperature	212°F (100°C)
Seat	EPDM stem seat and gasket
Size	2"

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Weight Lb	1.3850

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us