BAYONET STYLE DRY DISCONNECT ADAPTER X FEMALE NPT



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/24/2026 12:46 AM

SKU
: 8702

BRAND
: DIXON VALVE

MODEL
: BA61-300

Applications:
Bayonet dry disconnect fittings are ideally suited for the spill-less transfer of petroleum products such as fuel oil, lube oil blending, and tank truck delivery. The design of the Bayco bayonet dry disconnect system ensures a spill free connection, fluid cannot flow until couplings are connected together and the valve is opened. The coupling can then not be disconnected until the valve handle is closed.

Specifications:
Canadian registration number CRN# OH14055 all provinces

Features:
Helps eliminate the possibility of costly spills

Construction:
Anodized aluminum poppet valve

Compatibility & Interchange Data:
Interchangeable with the Emco Wheaton™ Dry Break™

Note:
Rubber dust caps with stainless steel chains are available to protect the adapter from contamination and damage.

Safety notes:
For pressure ratings at other temperatures contact Dixon®.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Factory Part Number	BA61-300
Material	Aluminum
Maximum Operating Pressure	85 PSI at 70°F (21°C)
Seal	Buna
Size	3"
Weight Lb	2.6000

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us