# BAYONET STYLE DRY DISCONNECT ADAPTER X FEMALE NPT




** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/24/2026 12:58 AM

SKU
: 8703

BRAND
: DIXON VALVE

MODEL
: BA62-300

Applications:
Bayonet dry disconnect fittings are ideally suited for the spill-less transfer of petroleum products such as fuel oil, lube oil blending, and tank truck delivery. The design of the Bayco bayonet dry disconnect system ensures a spill free connection, fluid cannot flow until couplings are connected together and the valve is opened. The coupling can then not be disconnected until the valve handle is closed.

Specifications:
Canadian registration number CRN# OH14055 all provinces

Features:
Helps eliminate the possibility of costly spills

Construction:
Anodized aluminum poppet valve

Compatibility & Interchange Data:
Interchangeable with the Emco Wheaton™ Dry Break™

Note:
Rubber dust caps with stainless steel chains are available to protect the adapter from contamination and damage.

Safety notes:
For pressure ratings at other temperatures contact Dixon®.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov



2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

## TECHNICAL SPECIFICATIONS

| | |
|---|---|
| **Factory Part Number** | BA62-300 |
| **Material** | Aluminum |
| **Maximum Operating Pressure** | 85 PSI at 70°F (21°C) |
| **Seal** | FKM |
| **Size** | 3" |
| **Weight Lb** | 2.5800 |



KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us