BR-SERIES PNEUMATIC FEMALE THREADED PLUG





** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 06:19 PM

SKU
: 9130

BRAND
: DIXON VALVE

MODEL
: BR1F1-B-E-7

Construction:
Machined components are manufactured using solid brass bar stock.
Machined components are plated with chrome-over-nickel plating.

Compatibility & Interchange Data:
Rectus 21KA, Tomco Series SC, CEJN Series 223

Safety notes:
It is important to be safe when installing quick disconnect couplings into a pneumatic circuit. Never install a pneumatic coupling directly into an air tool, use a piece of hose that is at least 18" long, between the tool and the coupling, to prevent damage to the coupling. To protect the operator, safety devices, such as a safety check valve and safety cable should be installed in case there is a hose or coupling failure.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	1/8"
Burst Pressure	7000 PSI
Factory Part Number	BR1F1-B-E-7
Hex	9/16"
Length	1.14"
Material	Brass
Maximum OD	0.65"
Maximum Operating Pressure	300 PSI
Temperature Range	-40°F to +250°F (-40°C to +121°C)

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Thread	NPT
Thread Size	1/8"
Weight Lb	0.0400

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us