SAND BLAST QUICK COUPLING



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 05:07 PM

SKU
: 9288

BRAND
: DIXON VALVE

MODEL
: BSB150

Applications:
Sand blast couplings are designed for use on sand blast hose.

Features:
Supplied with screws

Installation
Ends of hose must be cut square to fit snug against metal end.
Holding hose tight to end of fitting, insert screws and turn in full, putting screw 180° from first to ensure best centering.
After all screws have been placed, check tube opposite screws to be sure screws have not penetrated completely through.
On quick couplings, insert safety clips.

Safety notes:
Abrasive blasting equipment must have hose safety cables or hose coupling safety clips installed
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	BSB150
Hose OD	2-3/8"
Hose Size	1-1/2"
Material	Brass
Pressure Rating	110 PSI at ambient temperature 70°F (21°C)
Weight Lb	2.0300

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us