3-WAY MULTI-PORT SANITARY STAINLESS STEEL BALL VALVE



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/24/2026 12:55 AM

SKU
: 9741

BRAND
: DIXON VALVE

MODEL
: BV3SCTF100C-A

Specifications:
Break torque: 207 in. lbs.

Features:
Full port design
Blow-out proof stem
Live-loaded stem packing
Lock-out, tag out

Construction:
CF8M stainless body, ends and ball
25% carbon reinforced tetrafluoroethylene seat is specified for higher temperature pressure applications. Ideal for steam and thermal fluid applications. Higher cycle life than RTFE.
ISO 5211 mounting pad

Available Options:
Private label handle covers available

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Factory Part Number	BV3SCTF100C-A
Material	Stainless Steel
Port	T Port
Pressure Rating	650 PSI WOG
Seat	25% carbon reinforced PTFE
Size	1"

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us