WILKERSON FRL'S C08 MINIATURE COMBINATION UNIT



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 08:05 PM

SKU
: 26122

BRAND
: DIXON VALVE

MODEL
: C08-02M

Features:
Manual Drain
Transparent Bowl and Guard
F08 series Filter has a 5 micron element and a.4 oz. bowl
R08 series Regulator is self-relieving with a balanced valve design, it has a 0-125 PSI adjusting range and is supplied with a 0-160 PSI flush mount style gauge
L08 series Lubricator has a.6 oz. bowl, an adjustable oil feed and a full view sight dome
(2) mounting brackets with joiner set are included

Safety notes:
FRL\'s are designed for air service only, unless otherwise indicated.
SCFM ratings at 150 PSIG inlet pressure
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Description	Manual Drain, Transparent Bowl and Guard
Factory Part Number	C08-02M
Flow	27 SCFM
Mandatory Pkg/Box Qty	1
Maximum Operating Pressure	150 PSIG (10.3 Bar)
Port	1/4"
Temperature Range	32°F to 125°F (0°C to 52°C)
Weight Lb	1.8750

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us