WILKERSON FRL'S C16 COMPACT COMBINATION UNIT



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 06:53 PM

SKU
: 26141

BRAND
: DIXON VALVE

MODEL
: C16-04M

Features:
Manual Drain
Transparent Bowl and Guard
F16 series Filter has a 5 micron element and 5 oz. bowl
R16 series Regulator is self relieving, has a 0-125 PSI adjusting range and is supplied with a GC230 gauge
L16 series Lubricator has a 5 oz. bowl, an adjustable oil feed and a full view sight dome
(2) modular sleeves, (2) mounting brackets (sleeve and bracket) and (2) end blocks are included

Safety notes:
FRL\'s are designed for air service only, unless otherwise indicated.
SCFM ratings at 150 PSIG inlet pressure
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Description	Manual Drain, Transparent Bowl and Guard
Factory Part Number	C16-04M
Flow	64.0 SCFM
Mandatory Pkg/Box Qty	1
Maximum Operating Pressure	150 PSIG (10.3 Bar)
Port	1/2"
Temperature Range	32°F to 125°F (0°C to 52°C)
Weight Lb	6.4100

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us