GROOVED STANDARD COUPLING- SERIES S, STYLE 11



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 08:32 PM

SKU
: 23377

BRAND
: DIXON VALVE

MODEL
: C18BU

Applications:
Designed for a wide range of applications including commercial/industrial construction, mining, and process piping.

Specifications:
Underwriters Listed
Factory Mutual approved
Bolts: 2
Bolt Size: 7/8"
Bolt Length: 5"

Features:
Housing design allows for optimum strength without excessive casting weight
Comparable to Victaulic's #77 and Grinnell's #7001

Construction:
Rust inhibiting paint

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Factory Part Number	C18BU
Material	Ductile Iron
Max. End Load Lbs.	46741
Maximum Operating Pressure	800 PSI at 70°F (21°C)
Nominal Size	8"
Pipe OD	8.625"
Seal	Buna-N
Weight Lb	21.6600

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us