WILKERSON FRL'S C26 STANDARD COMBINATION UNIT



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 08:04 PM

SKU
: 26162

BRAND
: DIXON VALVE

MODEL
: C26-04MMB

Features:
Manual Drain
Metal Bowl
F26 Series Filter has a 5 micron element and a 10 oz. bowl
F26 series Regulator is self-relieving with a 0-125 PSI adjusting range and is supplied with a GC230 gauge
L26 series Lubricator has a 10 oz. bowl, an adjustable oil feed and a full view sight dome
(2) modular sleeves, (2) mounting brackets (sleeve and bracket) and (2) end blocks are included

Safety notes:
FRL\'s are designed for air service only, unless otherwise indicated.
SCFM ratings at 150 PSIG inlet pressure
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Description	Manual Drain, Metal Bowl
Factory Part Number	C26-04MMB
Flow	128 SCFM
Mandatory Pkg/Box Qty	1
Maximum Operating Pressure	200 PSIG (13.8 Bar)
Port	1/2"
Temperature Range	32°F to 175°F (0°C to 79°C)
Weight Lb	9.9100

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us