HYDRAULIC 4-BOLT FLANGE NPTF PORT



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/24/2026 12:27 AM

SKU
: 9863

BRAND
: DIXON VALVE

MODEL
: C6143K4040NPT

Applications:
Flange adapters for hydraulic systems make installation of components easier, especially in applications with limited space.

Specifications:
SAE J518-1 / ISO 6162-1

Features:
Standard pressure
Flanges are constructed with an O-ring seal to eliminate leakage
Includes bolt kit with Buna O-ring

Construction:
Pad size: 2-1/2"

Available Options:
Also available in 316L stainless steel, contact Dixon

Note:
Connection type opposite 4-bolt flange connection can de-rate maximum working pressure

Safety notes:
Pressure rating given at ambient temperature 70°F
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Factory Part Number	C6143K4040NPT
Fitting Type	O-ring
Material	Carbon Steel
Maximum Operating Pressure	2500 PSI (17.5 MPa)
Port	2-1/2"
Style	Code 61
Thread Size	2-1/2"-8
Torque	Grade 8 UNC: 111 lb-ft
Weight Lb	3.6500

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us