HYDRAULIC 4-BOLT FLANGE NPTF PORT



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 11:42 PM

SKU
: 9930

BRAND
: DIXON VALVE

MODEL
: C62452020NPT

Applications:
Flange adapters for hydraulic systems make installation of components easier, especially in applications with limited space.

Specifications:
SAE J518-2 / ISO 6162-2

Features:
High pressure
Flanges are constructed with an O-ring seal to eliminate leakage
Flat face flange must be used with O-ring flange
No bolt kit is included with flat face flange

Construction:
Pad size: 1-1/4"

Available Options:
Also available in 316L stainless steel, contact Dixon

Note:
Connection type opposite 4-bolt flange connection can de-rate maximum working pressure

Safety notes:
Pressure rating given at ambient temperature 70°F
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Factory Part Number	C62452020NPT
Fitting Type	Flat Face
Material	Carbon Steel
Maximum Operating Pressure	6000 PSI (40 MPa)
Port	1-1/4"
Style	Code 62
Thread Size	1-1/4" - 11-1/2
Torque	Grade 8 UNC: 111 lb-ft
Weight Lb	2.8600

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us