# WILKERSON FRL'S CB6 COMPACT FILTER/REGULATOR



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 06:22 PM

SKU
: 26192

BRAND
: DIXON VALVE

MODEL
: CB6-04AG

Applications:
Over-under units are space savers and provide for installation in tight areas.
One common inlet/outlet for both filter and regulator saves on piping costs.

Use:
Two 1/4" gauge ports located on the front and rear faces of the body. These ports may be used as additional regulated ports or for pressure gauges. Plug unused port(s).

Features:
Automatic Drain
Transparent Bowl and Guard
0-125 PSIG adjusting range
5 micron reusable element
5 oz. bowl
Self-relieving standard
Diaphragm operated
Quick-disconnect bowl guard with integral plastic bowl and safety latch standard
Supplied with a GC230 gauge

Safety notes:
FRL\'s are designed for air service only, unless otherwise indicated.
SCFM ratings at 100 PSIG inlet pressure
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov



2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

## TECHNICAL SPECIFICATIONS

| | |
|---|---|
| **Description** | Automatic Drain, Transparent Bowl and Guard |
| **Factory Part Number** | CB6-04AG |
| **Flow** | 70.0 SCFM |
| **Mandatory Pkg/Box Qty** | 1 |
| **Maximum Operating Pressure** | 150 PSIG (10.3 Bar) |
| **Port** | 1/2" |
| **Temperature Range** | 32°F to 125°F (0°C to 52°C) |
| **Weight Lb** | 2.5500 |



KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us