KING CRIMP® STYLE FERRULE 304 STAINLESS STEEL



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 11:11 PM

SKU
: 23401

BRAND
: DIXON VALVE

MODEL
: CF100-5SS

Use:
For use with crimp style shanks.

Safety notes:
Only use the crimp style shanks with the crimp style sleeves and ferrules. Due to differences in dimensions and tolerances for safety reasons, do not interchange other manufacturer's products with Dixon products.
Pressure rating given at 70°F, consult Dixon for pressure rating at elevated temperatures.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	CF100-5SS
Hose ID	1"
Hose OD From	1-29/64" (36.91mm)
Hose OD To	1-32/64" (38.10mm)
ID	1.563" (39.70mm)
Length	2-13/16"
Material	304 Stainless Steel
Wall Thickness	0.062
Weight Lb	0.2300
Working Pressure	250 PSIG with King Crimp Cam & Groove, 400 PSIG with King Crimp ST Nipple

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us