# KING CRIMP® STYLE FERRULE 304 STAINLESS STEEL




** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/24/2026 12:13 AM

SKU
: 23475

BRAND
: DIXON VALVE

MODEL
: CF300-14SS

Use:
For use with crimp style shanks.

Safety notes:
Only use the crimp style shanks with the crimp style sleeves and ferrules. Due to differences in dimensions and tolerances for safety reasons, do not interchange other manufacturer's products with Dixon products.
Pressure rating given at 70°F, consult Dixon for pressure rating at elevated temperatures.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

## TECHNICAL SPECIFICATIONS

| | |
|---|---|
| **Factory Part Number** | CF300-14SS |
| **Hose ID** | 3" |
| **Hose OD From** | 4-1/64" (102.00mm) |
| **Hose OD To** | 4-4/64" (103.19mm) |
| **ID** | 4.125" (104.78mm) |
| **Length** | 4" |
| **Material** | 304 Stainless Steel |
| **Wall Thickness** | 0.09 |
| **Weight Lb** | 1.3810 |
| **Working Pressure** | 150 PSIG with King Crimp Cam & Groove,<br/>300 PSIG with King Crimp ST Nipple |



2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us