KING CRIMP® STYLE FERRULE CARBON STEEL



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 10:57 PM

SKU
: 23482

BRAND
: DIXON VALVE

MODEL
: CF300-2CS

Use:
For use with crimp style shanks.

Safety notes:
Only use the crimp style shanks with the crimp style sleeves and ferrules. Due to differences in dimensions and tolerances for safety reasons, do not interchange other manufacturer's products with Dixon products.
Pressure rating given at 70°F, consult Dixon for pressure rating at elevated temperatures.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	CF300-2CS
Hose ID	3"
Hose OD From	3-17/64" (82.95mm)
Hose OD To	3-20/64" (84.14mm)
ID	3.375" (85.73mm)
Length	4"
Material	Carbon Steel
Wall Thickness	0.09
Weight Lb	1.0660
Working Pressure	150 PSIG with King Crimp Cam & Groove, 300 PSIG with King Crimp ST Nipple

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us