KING CRIMP® STYLE FERRULE HEAVY DUTY CARBON STEEL



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/24/2026 01:12 AM

SKU
: 23511

BRAND
: DIXON VALVE

MODEL
: CF400-14CSHD

Use:
For use with crimp style shanks.

Safety notes:
Only use the crimp style shanks with the crimp style sleeves and ferrules. Due to differences in dimensions and tolerances for safety reasons, do not interchange other manufacturer's products with Dixon products.
400 PSI working pressure with a minimum 4:1 safety factor (hose burst: hose working pressure) is only achieved with Dixon carbon steel ferrule part numbers CF400-6CSHD through CF400-16CSHD on Dixon Frac Fittings
Pressure rating given at 70°F, consult Dixon for pressure rating at elevated temperatures.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	CF400-14CSHD
Hose ID	4"
Hose OD From	5-1/64" (127.40mm)
Hose OD To	5-4/64" (128.60mm)
ID	5.125" (130.18mm)
Length	4" (102mm)
Material	Carbon Steel
Wall Thickness	0.12" (3.05mm)
Weight Lb	3.0000
Working Pressure	400 PSI

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us