CJ-SERIES PNEUMATIC MALE THREADED PLUG





** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 08:59 PM

SKU
: 10101

BRAND
: DIXON VALVE

MODEL
: CJ2BM2-B

Specifications:
Rated pressure for connected Brass Coupler & Brass Plug: 300 PSI (20 bar) Maximum Working and 7,200 PSI (500 bar) Burst

Construction:
Machined components are manufactured using solid brass bar stock.

Compatibility & Interchange Data:
European High-Flow Interchange
Interchanges with CEJN 320, Coilhouse Megaflow, Rectus 25KA/26KA and other like designs

Safety notes:
It is important to be safe when installing quick disconnect couplings into a pneumatic circuit. Never install a pneumatic coupling directly into an air tool, use a piece of hose that is at least 18" long, between the tool and the coupling, to prevent damage to the coupling. To protect the operator, safety devices, such as a safety check valve and safety cable should be installed in case there is a hose or coupling failure.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Body Size	1/4"
Factory Part Number	CJ2BM2-B
Hex	9/16"
Length	1.48" (37.5mm)
Material	Brass
Maximum OD	0.65" (16.5mm)
Pressure Rating	See Product Details
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Thread	BSPT
Thread Size	1/4"
Weight Lb	0.0500

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us