DQC CM-SERIES INDUSTRIAL MOLD INTERCHANGE PLUG FEMALE NPTF





** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 11:42 PM

SKU
: 10157

BRAND
: DIXON VALVE

MODEL
: CM3F2

Specifications:
Rated pressure for connected Brass Unvalved Coupler and Steel Plug: 500 PSI (35 bar) Maximum Working and 14,200 PSI (1,000 bar) Burst
Rated pressure for connected Brass Valved Coupler and Steel Plug: 500 PSI (35 bar) Maximum Working and 6,100 PSI (400 bar) Burst

Construction:
Machined components are manufactured using solid bar stock
Steel componentry is plated using ROHS Compliant Trivalent Chrome.

Compatibility & Interchange Data:
Mold Coolant Interchange
Foster Series- FJT, Hansen Flo-Temp, Tomco MC-Series, Parker Moldmate, DME Jiffy-Tite

Safety notes:
Maximum working and burst pressure is based on a coupled set, contact Dixon for pressure ratings.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	3/8"
Factory Part Number	CM3F2
Hex	5/8"
Length	1.34"
Material	Steel
Maximum OD	0.72"

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Temperature Range	-90°F to +400°F (-68°C to +205°C)
Thread	Female NPTF
Thread Size	1/4"-18
Weight Lb	0.0550

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us