DQC CM-SERIES INDUSTRIAL MOLD INTERCHANGE PLUG FEMALE NPTF





DATE
: 11/24/2026 03:09 AM

SKU
: 10175

BRAND
: DIXON VALVE

MODEL
: CM4F6-B

Specifications:
Rated pressure for connected Brass Unvalved Coupler and Brass Plug: 300 PSI (20 bar) Maximum Working and 4,900 PSI (340 bar) Burst

Construction:
Machined components are manufactured using solid bar stock

Compatibility & Interchange Data:
Mold Coolant Interchange
Foster Series- FJT, Hansen Flo-Temp, Tomco MC-Series, Parker Moldmate, DME Jiffy-Tite

Safety notes:
Maximum working and burst pressure is based on a coupled set, contact Dixon for pressure ratings.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	1/2"
Factory Part Number	CM4F6-B
Hex	1-3/16"
Length	1.69"
Material	Brass
Maximum OD	1.37" (34.8mm)
Temperature Range	-90°F to +400°F (-68°C to +205°C)
Thread	Female NPTF

** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Thread Size	3/4"-14
Weight Lb	0.1000

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us