DQC CVV-SERIES EUROPEAN INTERCHANGE FEMALE PLUG





** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/24/2026 12:52 AM

SKU
: 10366

BRAND
: DIXON VALVE

MODEL
: CVV3FM1615

Construction:
Machined components are manufactured using solid bar stock
Steel retaining rings and springs maximize service life in rugged environments.
Steel componentry is plated using ROHS Compliant Trivalent Chrome.
Nipples have a PTFE Anti-Extrusion ring to prevent O-Ring damage during dynamic impulse service.

Compatibility & Interchange Data:
European Screw-Together Interchange
Inteva STG-Series, Faster CVV-Series, DNP PVV3, Voswinkel Type-HS, Stucchi VD Series

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	3/8"
Burst Pressure	26000 PSI (1800 Bar)
Factory Part Number	CVV3FM1615
Hex	22mm
Length	2.52" (64.0mm)
Material	Steel
Maximum OD	1.10" (28.0mm)
Maximum Operating Pressure	6500 PSI (450 Bar)
Temperature Range	-40°F to +250°F (-40°C to +121°C)

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Thread	Female Metric
Thread Size	M16X1.5

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us