DQC H-SERIES ISO-B FOOD GRADE FEMALE THREADED PLUG





DATE
: 11/24/2026 12:19 AM

SKU
: 23770

BRAND
: DIXON VALVE

MODEL
: D-H4F4-S

Features:
Poppet style shut-off valves
Designed to prevent fluid loss when disconnected

Construction:
Machined components are manufactured using solid bar stock
Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.

Available Options:
Contact Dixon for all available option adders

Compatibility & Interchange Data:
Meets dimensional requirements of ISO 7241 Series B
Interchangeable with Parker-Hannifin 60 Series, Snap-Tite 72-Series, Hansen HK-Series, Faster Series 'HNV', Aeroquip/Eaton FD45, Stucchi Series IRB/IRBO/IRBX

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Body Size	1/2"
Burst Pressure	27500 PSI (1900 bar)
Factory Part Number	D-H4F4-S
Hex	1-1/16"
Length	1.94" (49.3mm)
Material	303 Stainless Steel
Maximum OD	1.17" (29.7mm)
Maximum Operating Pressure	3500 PSI (240 bar)
Temperature Range	-40°F to +400°F (-40°C to +204°C)
Thread	Female NPTF
Thread Size	1/2"-14
Weight Lb	0.2500

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us