WILKERSON FRL'S D28 COMBINATION UNIT



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 06:50 PM

SKU
: 26199

BRAND
: DIXON VALVE

MODEL
: D28-06MMB

Features:
Light weight, Ready-to-Mount assembly comes standard with pressure gauge and modular T-Bracket/Joiner Assembly
Components integrated into single unit
Modern design and appearance
Quick disconnect bowl / bowl guard
5 micron element
6.11 oz. bowl/lubricator
Regulator is self-relieving, with a 0-125 PSI adjusting range and is supplied with a gauge
2.87 oz. bowl/filter

Safety notes:
FRL\'s are designed for air service only, unless otherwise indicated.
SCFM ratings at 150 PSIG inlet pressure
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Description	Manual Drain, Metal Bowl with Sight Gauge
Factory Part Number	D28-06MMB
Flow	150 SCFM
Maximum Operating Pressure	250 PSIG (17.2 Bar)
Size	3/4"
Temperature Range	32°F to 150°F (0°C to 65.5°C)
Weight Lb	4.6500

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us