BAYLOC? DRY DISCONNECT ADAPTER X FEMALE NPT



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/24/2026 12:44 AM

SKU
: 11292

BRAND
: DIXON VALVE

MODEL
: DBA11-150

Applications:
Dry disconnects help prevent spillage from normal or accidental disconnects. A spring loaded sealing device is designed to "snap" closed should the valve become disconnected with the poppet open, significantly limiting liquid loss.
For use in transfer of hazardous fluids

Use:
Use with DBC or D2C style couplers
Use with standard cam and groove dust caps sized one size larger than the dry disconnect size
Use Cam & Groove Dust Cap Size: 2"

Features:
Two-piece adapter design for easy rebuilding of adapters

Compatibility & Interchange Data:
Compatible with most other brands of cam and groove style dry disconnects
Fully interchangeable with Kamvalok (OPW trademark) style fittings

Note:
Contact Dixon™ at 800-355-1991 for chemical compatibility, size, material selection and special configurations.

Safety notes:
For pressure ratings at other temperatures, contact Dixon™.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Adapter Size	2"
Description	Cam & Groove Style
Factory Part Number	DBA11-150
Female Thread	NPT
Female Thread Size	1-1/2"
Material	Zinc/Aluminum
Maximum Operating Pressure	210 PSI at 70°F(21°C)
Seal	Buna
Weight Lb	2.0400

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us