BAYLOC® DRY DISCONNECT COUPLER X FEMALE NPT

DATE
: 11/24/2026 01:20 AM

SKU
: 27445

BRAND
: DIXON VALVE

MODEL
: DBC67-150





** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

Applications:
Dry disconnects help prevent spillage from normal or accidental disconnects. A spring loaded sealing device is designed to "snap" closed should the valve become disconnected with the poppet open, significantly limiting liquid loss.
Use:
Use with DBA style adapters
Use with standard cam and groove dust plug sized one size larger than the dry disconnect size
Use Cam & Groove Dust Plug Size: 2-1/2"
Specifications:
Canadian registration number CRN # OH14044 all provinces
Features:
Coupler has automatic closing poppet assembly
Heavy duty construction provides long service life
Stainless steel handle allows product exposure to corrosive chemicals or washdown service
Strong handle attachment prevents bending of crank assembly
Dixon EZ Boss-Lock cam arms provide added security from accidental opening due to vibration or snagging. Very easy to use, just close the arms and they lock, to open simply lift the lever.
Construction:
Stainless steel internals
Heavy duty stainless steel handle, crank and link
Compatibility & Interchange Data:
Compatible with most other brands of cam and groove style dry disconnects
Fully interchangeable with Kamvalok (OPW trademark) style fittings
Note:
Contact Dixon™ at 800-355-1991 for chemical compatibility, size, material selection and special configurations.
Safety notes:
Must be used with a DBA (Dry Break Cam & Groove) Style adapter for coupler

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

to operate. Adapter sold separately.

For pressure ratings at other temperatures, contact Dixon™.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Coupler Size	2"
Description	Cam & Groove Style
Female Thread	NPT
Female Thread Size	1-1/2"
Material	Aluminum
Maximum Operating Pressure	210 PSI at 70°F(21°C)
Factory Part Number	DBC67-150
Seal	PTFE Encapsulated FKM

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us