AIR CHIEF AUTOMOTIVE COUPLER PUSH-ON HOSE BARB



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 11:45 PM

SKU
: 23837

BRAND
: DIXON VALVE

MODEL
: DC242L

Features:
Semi-automatic- pull sleeve to connect
Couplers shut-off when disconnected

Compatibility & Interchange Data:
Air chief automotive quick-connect couplers will interchange with the popular makes of automotive quick-connect fittings such as Amflo, Dill, Milton and Truflate.
Note: There are some makes which do not interchange with any others. If you plan to interchange these couplings, make sure you have plug ends with the proper configuration.

Safety notes:
Operating pressure for couplings utilizing hose barb connections may be dramatically reduced to that of the hose rating and/or hose end connection combination. Consult hose manufacturer's catalog for hose end connection ratings. If in doubt, test under controlled conditions for suitability to application. Dixon cannot assume liability for misapplication of production resulting in equipment down-time, lost production, and/or personal injury including death.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Body Size	1/4"
Factory Part Number	DC242L
Flow	37 CFM at 100 PSI
Hose ID	1/4"
Material	Brass
Pressure Rating	300 PSI
Temperature Range	-40°F to 250°F (-40°C to 121°C)
Weight Lb	0.1800

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us