DOUBLE CLAPPER SIAMESE CONNECTION BACK OUTLET



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 06:14 PM

SKU
: 11516

BRAND
: DIXON VALVE

MODEL
: DCS4025F-P

Applications:
Provides the required 500 GPM minimum to supplement the fire protection as an auxiliary inlet connection to the water supply. (250 GPM minimum per inlet.)

Specifications:
UL listed
Factory Mutual approved
ULC Listed

Features:
Exposed Fire Department Connections (FDC) provide an economical method of satisfying local fire codes.

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Branding	Auto-Sprinkler
Factory Part Number	DCS4025F-P
Finish	Polished
Inlet	(2) 2-1/2" female NST (NH)
Material	Cast Brass
Maximum Operating Pressure	175 PSI
Outlet	4" female NPT
Weight Lb	16.0000

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us