DRY EVOTEK COUPLINGS

DATE
: 11/23/2026 06:30 PM

SKU
: 11619

BRAND
: DIXON VALVE

MODEL
: DDEC150SS



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

Applications:
Specifically designed for use in the chemical industry
Rotating the coupling 120° clockwise opens the valves where the high pressure engagement between hose and tank unit ensures a strong connection

Specifications:
Working pressure 360 PSI at ambient temperature 70°F (21°C)

Features:
Low connecting forces even against pressure
Ergonomic handle (DN40 and bigger)
Good transmission ratio in the cam curve
Wide range of chemical resistance due to high-quality material selection
Minimized spillage during de-coupling

Construction:
Body: stainless steel 1.4404
Handle: PE (DN40 and bigger)
O-rings: FPM, NBR, EPDM, FFKM
Thread seal: PTFE, FDA and others upon request

Note:
1-1/2" and 2" couplers have handwheel

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

Approvals
PED 2014/68/EU 4.3
ATEX 2014/34/EU Category 3G

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Description	Coupler x Female NPT
Factory Part Number	DDEC150SS
Female Thread	NPT
Female Thread Size	1 1/2"
Size	89 mm

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us

www.kmxusa.us