# DIXON MANNTEK DRY DISCONNECT STEAM ADAPTER X FEMALE NPT




** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/24/2026 02:05 AM

SKU
: 23879

BRAND
: DIXON VALVE

MODEL
: DDSA200SS

Applications:
Designed to fit hoses carrying steam used in chemical (heating), pharmaceutical (disinfection and sterilization) and at loading bays.

Features:
Unintentional separation is eliminated preventing accidents and avoiding unintended down time
Performance unaffected by surface rust

Construction:
Coupling housing and all inner parts: stainless steel
Seals: EPDM 291

Available Options:
Lockable versions are available on 1-1/2" and 2", contact Dixon
Other seal materials are available, contact Dixon

Safety notes:
Note. Pressurized steam is an extremely dangerous commodity. Only hose, fittings, clamps and accessory items that have been approved for steam service should ever be used! Never use an unapproved item for steam service. Always follow the manufacturer's product recommendations for pressurized steam handling.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov



KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

## TECHNICAL SPECIFICATIONS

| | |
|---|---|
| **Body Size** | 70mm |
| **Female Thread** | NPT |
| **Female Thread Size** | 2" |
| **Material** | 316 Stainless Steel |
| **Maximum Operating Pressure** | 150 PSI |
| **Maximum Temperature** | 350°F (177°C) |
| **Factory Part Number** | DDSA200SS |
| **Seal** | EPDM 291 |
| **Weight Lb** | 2.6400 |



KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us