# DF-SERIES CARTRIDGE ELEMENTS- PES MEMBRANE



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 08:25 PM

SKU
: 11637

BRAND
: DIXON VALVE

MODEL
: DF-PESE5E4S

Specifications:
Maximum differential pressure: 45 PSID
Maximum operating pressure: 45 PSID
Cartridge Element Lengths: 10" to 40"
Micron ratings:.1,.22,.45,.60. 80, 1.2 and 5.0

Features:
FDA title 21 compliant
Cartridge elements are constructed in a clean room environment
Cartridge elements have excellent dirt holding capacity with low flow resistance
Cartridge elements are free of surfactants, resins, binders, and adhesives
Low protein binding and chemical compatibility
Naturally hydrophilic media does not need wetting before use

Construction:
Cartridge element: polethersulfone; core material: polypropylene
Gasket/O-Ring: Buna, FKM, PTFE, silicone, neoprene, and EPDM

Note:
All sizes are 6pcs/case and sold in case quantities only.
There are many more options, including industrial housing and cartridge elements. All cartridge elements are manufactured to industry standards and are interchangeable with other manufacturers' products. Please call Dixon Sanitary 800.789.1718 for further information.

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov



2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

## TECHNICAL SPECIFICATIONS

| | |
|---|---|
| **Cartridge Element Length** | 20" |
| **Case** | Case Qty: 6 pieces |
| **Diameter** | 2.65" OD/ 1" Center ID |
| **Material** | Polyethersulfone/Polyproplyene/Silicone |
| **Micron Rating** | .22 |
| **Factory Part Number** | DF-PESE5E4S |
| **Style** | Hard Cage/222/Closed |



KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us

www.kmxusa.us