DF-SERIES CARTRIDGE ELEMENTS- HIGH EFFICIENCY PLEATED



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 07:50 PM

SKU
: 11651

BRAND
: DIXON VALVE

MODEL
: DF-PHEBF74S

Specifications:
Retention rating of 99.98%
Recommended change out differential pressure: 35 PSID (2.4 bar)
Cartridge Element Lengths: 9.75" to 40"
Micron ratings:.2,.45, 1, 3, 5, 10, 25, and 50
Available in hard carge (standard) or netted cage

Features:
FDA title 21 compliant
Cartridge elements are constructed in a clean room environment
Cartridge elements are free of surfactants, resins, binders, and adhesives

Construction:
Cartridge element: polypropylene
Gasket/O-Ring: Buna, FKM, PTFE, silicone, neoprene, and EPDM

Note:
All sizes are 6pcs/case and sold in case quantities only.
There are many more options, including industrial housing and cartridge elements. All cartridge elements are manufactured to industry standards and are interchangeable with other manufacturers' products. Please call Dixon Sanitary 800.789.1718 for further information.

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Cartridge Element Length	30"
Case	Case Qty: 6 pieces
Diameter	2.65"
Material	Polypropylene, Silicone
Micron Rating	.45
Factory Part Number	DF-PHEBF74S
Style	Hard Cage/222/Closed
Weight Lb	10.0000

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us