UL BIG MOUTH? DIESEL NOZZLE WITH SAFETY VALVE



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/24/2026 12:46 AM

SKU
: 11678

BRAND
: DIXON VALVE

MODEL
: DFN100-NPNF

Applications:
Truck stops

Specifications:
UL listed for use with Gas 10% Ethanol blend and diesel

Features:
Lightweight but strong
Micro-touch valve provides smooth operation and exceptional flow control
Roto-matic latch pin provides positive auto shut-off
Pure PTFE packing eliminates stem leaks
Super tough nylon hand guard
Snap-on handle cover makes changing scuff guards easy.
Yellow scuff guard
Trigger hold open clip
"no pressure, no flow" safety valve

Construction:
Body and spout: Aluminum
Body caps: Zinc
Seals: FKM/ Nitrile
Poppet Disk: FKM
Stem Packing: PTFE
Trigger: Steel
Snap-on Cover: Plastic
Scuff Guard: Vinyl

Safety notes:
These nozzles are not for use with gravity flow tanks (for gravity flow please see our 900 series nozzles)
Not designed for use with small 12 volt pumps, AC utility pumps, farm pumps

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Flow	27 GPM at 20 PSI
Inlet	1" female NPT
Intended Service	Diesel
Outlet	1-1/8" spout
Factory Part Number	DFN100-NPNF
Weight Lb	3.7500

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us