UL FUELMASTER DIESEL NOZZLE



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 08:43 PM

SKU
: 23889

BRAND
: DIXON VALVE

MODEL
: DFN100SF-NC

Applications:
Truck stops and terminal operations

Specifications:
UL listed for use with Gas 10% Ethanol blend and diesel

Features:
High flow capacity
Micro-touch valve provides smooth operation and exceptional flow control.
Roto-matic latch pin provides positive auto shut-off
Pure PTFE packing eliminates stem leaks
Super tough nylon hand guard
Easy to change 'locknut style' spout assembly
Green scruff guard

Construction:
Body and spout: Aluminum
Body caps: Zinc
Seals: FKM
Poppet disk: FKM
Stem packing: PTFE
Handguard: Super tough nylon
Trigger: Steel
Snap-on cover: Plastic
Scuff guard: Vinyl

Safety notes:
Not designed for use with gravity flow tanks, small 12 volt pumps, AC utility pumps, farm pumps or consumer pumps
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Flow	45 GPM at 20 PSI
Inlet	1" female NPT
Intended Service	Diesel
Material	Aluminum
Outlet	1-3/16" spout
Factory Part Number	DFN100SF-NC
Weight Lb	4.0000

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us