KF BORED FLANGE



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 07:11 PM

SKU
: 23935

BRAND
: DIXON VALVE

MODEL
: DVF-A25GA

Applications:
Vacuum sealing for ½"- 2" OD tubing in the semiconductor industry

Specifications:
Maximum temperature: 302°F (150°C)
Helium leakage testing to 1x10-8 Torr
Standards followed: ISO2681

Features:
Each assembly contains two identical flanges and a centering ring assembly and is clamped together with a thumbscrew clamp
Coupling features prevent O-ring collapse and keep the assembly aligned
KF flanges are compatible with other ISO-KF-QF vacuum flange manufacturers' components
All fittings are IPA cleaned and bagged in a controlled environment
MTR's available

Construction:
Fittings: 304 or 316L stainless steel
Clamps: aluminum
O-ring: FKM

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Flange Size	KF25
Material	304 Stainless steel
Factory Part Number	DVF-A25GA
Weight Lb	0.0670

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us

www.kmxusa.us