DQC E-SERIES STRAIGHT THROUGH INTERCHANGE FEMALE PLUG

DATE
: 11/23/2026 07:20 PM

SKU
: 12057

BRAND
: DIXON VALVE

MODEL
: E16F16-S





** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

Features:
Straight-Through Pressure-Wash Interchange
Interchanges with Parker ST-Series, Foster FST-Series, Tomco Series-ST, Hansen ST-Series
These plugs have no internal valves, providing maximum flow with minimum pressure drop.

Construction:
Machined components are manufactured using 303 stainless steel bar stock

Safety notes:
Do Not Disconnect with pressure in line.
Dixon cannot assume liability for misapplication of products resulting in equipment down-time, lost production, property damage and/or personal injury including death.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	2"
Burst Pressure	8,000 PSI (552 Bar)
Factory Part Number	E16F16-S
Female Thread	NPTF
Female Thread Size	2"-11-1/2
Hex	2-5/8"
Length	3.00 (76.2mm)
Material	303 Stainless Steel

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Maximum OD	3.03 (77.0mm)
Maximum Operating Pressure	2,000 PSI (138 Bar)
Weight Lb	1.3800

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us