DQC E-SERIES STRAIGHT THROUGH INTERCHANGE FEMALE PLUG





** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 05:21 PM

SKU
: 12067

BRAND
: DIXON VALVE

MODEL
: E2F2

Features:
Straight-Through Pressure-Wash Interchange
Interchanges with Parker ST-Series, Foster FST-Series, Tomco Series-ST, Hansen ST-Series
These plugs have no internal valves, providing maximum flow with minimum pressure drop.

Construction:
Machined components are manufactured using solid steel
Steel componentry is plated using ROHS Compliant Trivalent Chrome
Steel nipples are hardened to provide heavy duty performance.

Safety notes:
Do Not Disconnect with pressure in line.
Dixon cannot assume liability for misapplication of products resulting in equipment down-time, lost production, property damage and/or personal injury including death.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	1/4"
Burst Pressure	22,000 PSI (1,517 Bar)
Factory Part Number	E2F2
Female Thread	NPTF
Female Thread Size	1/4"-18
Hex	11/16"
Length	1.47 (37.3mm)

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Material	Steel
Maximum OD	0.79 (20.1mm)
Maximum Operating Pressure	5,500 PSI (379 Bar)
Weight Lb	0.0700

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us