DQC E-SERIES STRAIGHT THROUGH INTERCHANGE HOSE BARB PLUG

DATE
: 11/23/2026 06:43 PM

SKU
: 23985

BRAND
: DIXON VALVE

MODEL
: E6S6





** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

Features:
Straight-Through Pressure-Wash Interchange
Interchanges with Parker ST-Series, Foster FST-Series, Tomco Series-ST, Hansen ST-Series
These plugs have no internal valves, providing maximum flow with minimum pressure drop.

Construction:
Machined components are manufactured using solid steel
Steel componentry is plated using ROHS Compliant Trivalent Chrome
Steel nipples are hardened to provide heavy duty performance.

Safety notes:
Do Not Disconnect with pressure in line.
Dixon cannot assume liability for misapplication of products resulting in equipment down-time, lost production, property damage and/or personal injury including death.
Operating pressures for the standard hose barbs utilizing hose barb end connections may be dramatically reduced to that of the hose rating and/or hose and end connection combination. Consult hose manufacturer's catalog for hose end connection ratings. If in doubt, test under controlled conditions for suitability to application.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Burst Pressure	10,800 PSI (745 Bar)
Factory Part Number	E6S6
Hose ID	3/4"
Length	3.66" (92.96mm)
Material	Steel
Maximum OD	1.13 (28.7mm)
Maximum Operating Pressure	2,700 PSI (186 Bar)
Weight Lb	0.2100

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us