E73 SERIES 1 FRL'S COMPACT COMBINATION UNIT



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 05:07 PM

SKU
: 26202

BRAND
: DIXON VALVE

MODEL
: E73-3A

Applications:
These units are intended for use in industrial compressed air systems only.

Use:
Not for use with fluids
They must not be used where pressure or temperature may exceed maximum rated operating conditions.

Features:
Automatic Drain
Transparent Bowl
4 oz. reservoir
Supplied with a GC230 gauge
Supplied with micro-fog lubricators
Includes 2 clamps and wall mounting brackets # 4314-52, 2 clamps # 4314-51 and 2 NPT pipe adapters #4315-01.

Installation
Connected modularly

Safety notes:
FRL\'s are designed for air service only, unless otherwise indicated.
The polycarbonate plastic bowls used on these units can be damaged and possibly burst if exposed to such substances as certain solvents, strong alkalis, compressor oils that contain ester-based additives or synthetic oils. Fumes of these substances in contact with polycarbonate bowl, externally and internally, can also result in damage.
Use metal bowl in applications where a plastic bowl might be exposed to substances that are incompatible with polycarbonates.
Clean plastic bowl is warm water only.
SCFM ratings at 90 PSIG inlet pressure

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Description	Automatic Drain, Transparent Bowl
Factory Part Number	E73-3A
Flow	70 SCFM
Inlet Pressure	150 PSI
Mandatory Pkg/Box Qty	1
Maximum Temperature	125°F (51°C)
Port	3/8"
Pressure Range	5-150 PSI
Weight Lb	6.3510

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us