DQC E-SERIES STRAIGHT THROUGH INTERCHANGE MALE PLUG





** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 10:25 PM

SKU
: 12098

BRAND
: DIXON VALVE

MODEL
: E8M8

Features:
Straight-Through Pressure-Wash Interchange
Interchanges with Parker ST-Series, Foster FST-Series, Tomco Series-ST, Hansen ST-Series
These plugs have no internal valves, providing maximum flow with minimum pressure drop.

Construction:
Steel componentry is plated using ROHS Compliant Trivalent Chrome
Steel nipples are hardened to provide heavy duty performance.

Safety notes:
Do Not Disconnect with pressure in line.
Dixon cannot assume liability for misapplication of products resulting in equipment down-time, lost production, property damage and/or personal injury including death.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	1"
Burst Pressure	8,000 PSI (552 Bar)
Factory Part Number	E8M8
Hex	1-3/8"
Length	2.45 (62.2mm)
Male Thread	NPTF
Male Thread Size	1" - 11-1/2
Material	Steel

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Maximum OD	1.59 (40.4mm)
Maximum Operating Pressure	2,000 PSI (138 Bar)
Weight Lb	0.3900

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us