EZLINK? ARMLESS CAM & GROOVE TYPE C COUPLER X HOSE SHANK





** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 11:54 PM

SKU
: 12269

BRAND
: DIXON VALVE

MODEL
: EZL400-C-AL

Applications:
Transfer and/or unloading of fuels (gasoline or diesel) from tank truck to storage tanks
Transfer of liquids compatible with the available coupling and gasket materials

Features:
Automatic couplers push-to-connect providing a reliable connection
Low profile allows easy connection and disconnection in tight applications
Coupler push tabs can be locked with safety pins and/or zip tie
Compatible with standard cam and groove adapters
EZLink™ stainless steel tabs are guaranteed for life! Should you ever break one return it to the nearest warehouse for a free replacement.

Construction:
Couplings: A356 Aluminum
Coupler tabs and springs: 316 stainless steel
Gasket: Buna-N

Safety notes:
Only use EZLink™ gaskets and tabs for this coupling system. Traditional cam & groove handles and gaskets, or other types of seals are not compatible and will fail.
Warning: Failure to follow the recommended procedures may result in serious injury and property damage.
Pressure rating recommendations are based on the use of mating Dixon fittings at ambient temperature 70°F / 21°C with a standard seal installed. For use at elevated temperature or other unusual operating conditions, consult Dixon.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Material	A356 Aluminum
Maximum Operating Pressure	150 PSI (with King Crimp? Ferrules), 110 PSI (with Crimp Sleeves), 100 PSI (with Band Clamps)
Factory Part Number	EZL400-C-AL
Seal	Buna-N Gasket
Size	4"
Temperature Range	Gasket: 5°F to 180°F (-15°C to 82°C)
Weight Lb	2.2000

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us