WILKERSON FRL'S F23 EXHAUST MUFFLER



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/24/2026 01:55 AM

SKU
: 26276

BRAND
: DIXON VALVE

MODEL
: F23-04M

Applications:
The contaminants in the exhaust flow are mechanically separated and twice filtered to 5 micron levels. The clean, muffled exhaust flows out of the unit under the metal hood on top.
Removes oily aerosols from exhaust flows

Features:
One inlet port
5 micron element
Quick disconnect clamp ring for easy bowl removal
Manual drain

Safety notes:
Designed for air service only, unless otherwise indicated!
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Description	Transparent Bowl with Guard
Factory Part Number	F23-04M
Flow	240 SCFM @ 90 PSI
Maximum Operating Pressure	150 PSIG (10.3 Bar)
Size	1/2"
Temperature Range	32°F to 125°F (0°C to 52°C)
Weight Lb	3.1200

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us