F74 SERIES 1 FRL'S OIL REMOVAL (COALESCING) FILTER



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/24/2026 01:36 AM

SKU
: 26359

BRAND
: DIXON VALVE

MODEL
: F74H-4A-MB

Features:
Automatic Drain
Metal Bowl
Quick-release bayonet bowl
Prismatic lens liquid level indicator
Provides air quality class 2 hydrocarbon and class 1 particulate removal per ISO 8573-1
Element removes particles down to 0.01mm. Maximum remaining oil content of air leaving the filter is 0.01 ppm at 70°F (21°C) with an inlet concentration of 8 ppm
Service life indicator turns from green to red when element needs to be replaced

Installation
In-line or modular installation

Note:
For maximum service life install a general purpose filter upstream of the oil removal filter.

Safety notes:
FRL\'s are designed for air service only, unless otherwise indicated.
SCFM ratings at 90 PSIG inlet pressure
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Description	High Flow
Factory Part Number	F74H-4A-MB
Flow	100 SCFM Dry, 60 SCFM Saturated
Inlet Pressure	250 PSI at 150°F (66°C)
Port	1/2"
Weight Lb	2.6200

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us