F74 SERIES 1 FRL'S OIL VAPOR REMOVAL FILTER



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/24/2026 02:17 AM

SKU
: 26361

BRAND
: DIXON VALVE

MODEL
: F74V-3A-MB

Use:
Provides air quality class 1 particulate removal per ISO 8573-1, when used with the F74C series
Minimum service life of 400 hours can be expected if the vapor removal filter is protected upstream by an oil removal (coalescing) filter and if the filtration temperature is in the region of 70° to 80°F (21° to 26°C). Above this range, oil vapor content of compressed air increases substantially and element service life is reduced.

Features:
Automatic Drain
Metal Bowl
Quick-release bayonet bowl
Activated carbon cartridge filter element absorbs oil vapors and removes most hydrocarbon odors.
Carbon cartridge element provides long service life.
Filter and element designs optimizes air velocity and contact time to reduce oil content of air leaving the filter to 0.003 ppm at 70°F (21°C).

Installation
In-line or modular installation

Note:
For maximum service life install a general purpose filter and an oil removal filter upstream of the oil vapor removal filter.

Safety notes:
FRL\'s are designed for air service only, unless otherwise indicated.
SCFM ratings at 90 PSIG inlet pressure
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Factory Part Number	F74V-3A-MB
Flow	21 SCFM
Inlet Pressure	250 PSI at 150°F (66°C)
Port	3/8"
Weight Lb	2.5000

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us