FORESTRY FOG NOZZLE



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 07:41 PM

SKU
: 12439

BRAND
: DIXON VALVE

MODEL
: FFN100

Specifications:
FFN100 meets USFS 5100-239A and NSN 4210-01-165-6603
Nozzle conforms to Forestry Service specification 5100-239C and 5100-107a

Features:
Dual flow rate nozzles offer two straight stream and two fog patterns
Combination fog and straight stream

Construction:
Maroon hard-coated barrel allows for easy identification
Corrosion resistant plated

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Female Thread	NPSH
Flow	12 GPM @ 100 PSI, 25 GPM @ 100 PSI (Straight Stream)
Material	6061-T6 Aluminum
Maximum Operating Pressure	600 PSI (water only) at 70°F (21°C)
Factory Part Number	FFN100
Size	1"
Weight Lb	0.8200

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us