MINI NEEDLE VALVE FEMALE TO FEMALE



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 10:52 PM

SKU
: 12445

BRAND
: DIXON VALVE

MODEL
: FFS102

Specifications:
Flow coefficient: 0.42
Metal-to-metal hard seat design is 100% helium leak tested to 1 x 10-4 ml/s at 200 PSI

Features:
A FKM O-ring seal and a PTFE back-up ring below the threads protects the mini valve from corrosion and galling.
Stem threads are rolled for strength and ease of operation

Construction:
316 Stainless Steel Stem

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Orifice	0.172"
Style	T Design Handle
Thread	NPT
Thread Size	1/4"-18
Factory Part Number	FFS102
Material	316 Stainless Steel
Pressure Rating	10000 PSI at 200°F (93°C)
Seal	FKM O-ring
Seat	Metal-to-Metal Hard Seat

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Weight Lb	0.3700

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us