FH-SERIES SANITARY FILTER HOUSINGS



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/24/2026 04:48 AM

SKU
: 12455

BRAND
: DIXON VALVE

MODEL
: FH-1-30B10CS

Applications:
Used for separating solid matter from liquid in the food processing, beverage, dairy, wineries and breweries, personal care products, and chemical markets.

Specifications:
150 PSI working pressure at 300°F (149°C)
1-1/2" clamp vent/gauge connection standard
1/2" clamp drain connection standard
222 or 226 cartridge elements
Clamp connection sizes: 1"- 4"
Number of elements: 1, 3, 5, 7, 12, and 21
Cartridge element lengths: 10", 20" 30", and 40"

Features:
Utilizes a heavy-duty stainless clamp closure for ease of element changes
High purity construction assures dependable protection for critical process applications
Custom OEM designs available
Large variety of cartridge elements available to meet your application needs

Construction:
Product contact: 316L stainless steel
32Ra OD polish; 25Ra ID polish
Silicone O-ring seals standard; FKM and EPDM options

Available Options:
Different finishes
Variety of connections

Note:
Cartridge elements are not included with the filter housings and must be

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ordered separately.

There are many more options, including industrial housings. Please call Dixon Sanitary 800.789.1718 for further information.

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Cartridge Element Length	30"
Intended Service	Number of Elements: 1
Material	316L Stainless Steel
Factory Part Number	FH-1-30B10CS
Seal	Silicone O-Ring
Size	1" Clamp
Style	Element Type: 226
Weight Lb	18.0000

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us