GLOBAL CAM & GROOVE TYPE F ADAPTER X MALE NPT



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/24/2026 02:04 AM

SKU
: 14472

BRAND
: DIXON VALVE

MODEL
: G50-F-SS

Applications:
Designed for use with liquids, consult Dixon for specific recommendations

Specifications:
No standard exists for the 1/2" fittings, and generally does not interchange with other manufacturers.

Features:
Made to Dixon specifications and branded Dixon

How it works:
To make a connection, simply slide the adapter into the coupler and with normal hand pressure, press the cam levers down.
Uncoupling is as quick and simple as coupling. Just lift the cam arms and remove the adapter.

Note:
Does not interchange in the 1/2" size with Dixon or Boss-Lock style cam and groove

Safety notes:
Under no circumstances should cam and groove couplings be used for compressed air or steam service!
Pressure rating is based on the seal of the mating part
Pressure rating recommendations are based on the use of mating Dixon fittings at ambient temperature 70°F / 21°C with a standard seal installed. For use at elevated temperature or other unusual operating conditions, consult Dixon.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Material	316 Investment Cast Stainless Steel
Maximum Operating Pressure	150 PSI
Factory Part Number	G50-F-SS
Size	1/2"
Weight Lb	0.1900

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us

www.kmxusa.us