GLOBAL CRIMP STYLE CAM & GROOVE TYPE C COUPLER X HOSE SHANK



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/24/2026 12:51 AM

SKU
: 24360

BRAND
: DIXON VALVE

MODEL
: G600-C-SSCR

Use:
Designed for use with liquids, consult Dixon for specific recommendations
Suitable for use with King Crimp sleeves and ferrules

Features:
Safety clips and a Buna-N gasket included

Available Options:
Other gasket types are available, contact Dixon.

Safety notes:
Under no circumstances should cam and groove couplings be used for compressed air or steam service!
Pressure rating recommendations are based on the use of mating Dixon fittings at ambient temperature 70°F / 21°C with a standard seal installed. For use at elevated temperature or other unusual operating conditions, consult Dixon.
Only use the crimp style shanks with the crimp style sleeves and ferrules. Due to differences in dimensions and tolerances for safety reasons, do not interchange other manufacturer's products with Dixon products.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Factory Part Number	G600-C-SSCR
Material	316 Investment Cast Stainless Steel
Maximum Operating Pressure	75 PSI
Seal	Buna-N
Size	6"
Weight Lb	15.0000

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us